

BUNDED 1300 LITRE TITAN ECOSAFE HORIZONTAL OIL TANK

The Kingspan Titan EcoSafe range of bunded oil tanks have long been the brand of choice and market leader in the industry. Suitable for domestic, commercial and agricultural heating requirements they safeguard properties against potential oil spills or ground contamination - future proofing your overall heating installation and reducing the risk of costly fines.



PRODUCT RANGE DETAILS

| Oil Level Alarm Monitor Capacity Ltr/Gal Length (mm) 1920 Width (mm) Height (mm) 1300 Guarantee Period 10 Years (one year on components) OFCERT N. O642109918 Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 Outlet Size 1" | | |
|--|-------------------------|--|
| Length (mm) Width (mm) 1230 Height (mm) 1300 Guarantee Period 10 Years (one year on components) OFCERT N. 0642109918 Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dily English (Cap) Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Oil Level Alarm Monitor | Watchman Alarm Fitted as Standard |
| Width (mm) 1230 Height (mm) 1300 Guarantee Period 10 Years (one year on components) OFCERT N. 0642109918 Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Capacity Ltr/Gal | 1300/285 |
| Height (mm) Guarantee Period 10 Years (one year on components) OFCERT N. O642109918 Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dillows Filter Fuel Type Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Length (mm) | 1920 |
| Guarantee Period 10 Years (one year on components) 0642109918 Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Width (mm) | 1230 |
| OFCERT N. Odd2109918 Duter Tank 16" Cap, Inner Tank 4" Inspection Cap Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Height (mm) | 1300 |
| Lids Outer Tank 16" Cap, Inner Tank 4" Inspection Cap Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Samp; Filter Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Guarantee Period | 10 Years (one year on components) |
| Tank Pack Watchman Alarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Dil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | OFCERT N. | 0642109918 |
| Fuel Type Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Lids | · · · · · · · · · · · · · · · · · · · |
| Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS EN14214 | Tank Pack | · · · · · · · · · · · · · · · · · · · |
| Outlet Size 1" | Fuel Type | Oil/Diesel (D) as defined in BS2869 and BS EN590 including upto 7%biofuel to BS |
| | Outlet Size | 1" |



EnergyStorage Solutions KINGSPAN TITAN

| Overfill Prevention | SpillStop device as standard |
|-----------------------|---|
| Regulation Compliance | The Control of Pollution (Oil Storage) (England) Regulations 2001, The Water Environment (Oil Storage) (Scotland) Regulations 2006 and Comparable Requirements throughout UK and Ireland. |
| Optional Accessory | Tigerloop Oil De-Aerator OFCERT N. 2181080901 |

OVERVIEW

FEATURES

Integrally Bund area holds 110% of the inner tank capacity.

Primary Tank secured in position, reducing stress on fittings.

SpillStop Overfill device fitted as standard - regulatory requirement.

Watchman Alarm oil level monitor Tank Pack supplied as standard.

100%End of Life recyclable.

Top outlet and bottom outlet options available.

Bund drain off point to remove any liquid contained in the bund.

BENEFITS

10 year guarantee (one year on equipment)

Double skin means double security eliminating the risk of leaks and spillage.

Low maintenance - no rust, no painting required.



EnergyStorage Solutions KINGSPAN TITAN

Remote oil level monitor fitted as standard reduces the possibility of running out of fuel for complete control over your heating bills.

Top outlet and bottom outlet options for easy access.

OFCERT approved and certified and manufactured to ISO standards.

All Kingspan Titan oil tanks covered by the CPR are now CE marked.

